



Eutech - PC Testr 35 combi waterproof

No need to change sensor every time you switch parameters - One tester measures five parameters (measures pH, Conductivity, TDS, Salinity and Temperature)

- * Full pH range measurement at up to 2-decimal places.
- * Low, medium and high Conductivity/ TDS ranges – tester measures pure water!
- * Multi-range Salinity measurements of up to 10.00 ppt or 1.00 %
- * Up to 5-point pH calibration and 3-point Conductivity/ TDS/ Salinity calibration.
- * Adjustable TDS factor (0.40 to 1.00) and Temperature Coefficient Feature (0.0 to 10.0%)
- * Temperature sensor housed within unique dome-shaped casing for faster ATC response and faster measurements.
- * ATC/ MTC option
- * Scroll-menu with four buttons control for stress-free navigation
- * Longest-lasting tester in the market! No tools required to replace sensor.
- * "One-press Parameter Toggle": Switching parameters is just a press of the button.
- * Certified IP67 Waterproof – Lightweight tester even floats for easy retrieval.



Link: www.kiwiland.com/growshop/control-measure/eutech-pc-testr-35-combi.html

Attributes

Category	Control & Measure
Sub category	PH & EC control
Brand	Eutech

Specifications

pH Range	0.00 to 14.00
pH Resolution	0.01 pH
Accuracy	±0.01 pH
pH Calibration Points	Up to 5 (Auto)pH Buffer Options

USA NIST	to 199.9 $\mu\text{S}/\text{cm}$
Conductivity Range	200 to 1999 $\mu\text{S}/\text{cm}$ 200 to 1999 $\mu\text{S}/\text{cm}$
Resolution	0.1 $\mu\text{S}/\text{cm}$ 1 $\mu\text{S}/\text{cm}$ 0.01 mS/cm
Accuracy	$\pm 1\%$ Full Scale Conductivity
Calibration Points	3 Auto 3 Manual
Normalization	25.0 $^{\circ}\text{C}$
Temperature	
Temperature	0.0 to 10.0%/ $^{\circ}\text{C}$
Coefficient	
Auto-Ranging	Yes
TDS Range	0.0 to 99.9 ppm 100 to 999 ppm 1.00 to 10.00 ppt
Resolution	0.1 ppm / 1 ppm / 0.01 ppt
Accuracy	1 % Full Scale
TDS Calibration	Up to 3 Points (Manual)
Points	
TDS Factor	0.40 to 1.00
Salinity Range	0.0 to 99.9 ppm 100 to 999 ppm 1.00 to 10.00 ppt 0.0 to 1.00 %
Resolution	0.1 ppm / 1 ppm / 0.01 ppt / 0.01%
Accuracy	1 % Full Scale
Salinity Calibration	Up to 3 (Manual)
Points	

Specifications

Salinity Calibration	0.0 to 50.0 $^{\circ}\text{C}$ / 32.0 to 120.0 $^{\circ}\text{F}$
Points	
Resolution	0.1 $^{\circ}\text{C}/^{\circ}\text{F}$
Accuracy	$\pm 0.5^{\circ}\text{C}/ \pm 0.9^{\circ}\text{F}$
Temperature	ATC / MTC
Compensation	
Non-Volatile	Yes
Memory	
Auto-Off	8.5 mins after last key pressed (can be disabled)
LCD Display	Dual-display LCD (2.1 x 2.7cm)

Power	4 X 1.5 V "A76" Micro alkaline batteries
Batter Life	> 150 hours

Price table

Product label	Product code	Price exc.	Vat	Price inc.
meter+electrode	GCON1014	219,30 euro	21.0 %	265,35 euro
electrode	GCON1015	86,78 euro	21.0 %	105,00 euro